

FENDT FIXED CHAMBER ROUND BALERS.

Equipment variants and technical details.

		1125 F	2125 F	2125 F Profi
General data				
Baler chamber diameter	m	1,25	1,25	1,25
Baler chamber width	m	1,23	1,23	1,23
Baler chamber volume	m ³	1,50	1,50	1,50
PowerGrip rollers	Number	18	18	18
Overall height	m	2,75	2,76	2,76
Overall length	m	4,95	4,98	4,98
Overall width	m	2,30	2,32	2,32
Weight	kg	3.300	3.200	3.400
Power requirement	kW/hp	40 / 60	65 / 85	50 / 80
Drive/gearbox				
Power Split gearbox		■	■	■
PTO drive	rpm	540	540	540
Implement driveline with free wheel and cam clutch		□	■	■
WW implement driveline		■		
Implement driveline with free wheel and WW joint		□		
Automatic chain lubrication		■	■	■
Lifetime lubricated roller bearings		■		
Bearing lubricated by lubricating points on both sides		□	■	■
Automatic roller lubrication			□	□
Drawbar				
Height-adjustable traction drawbar		■	■	■
Rigid drawbar eye hitch		□	□	□
Turnable drawbar eye hitch		■	■	■
K80 hitch		□	□	□
Pick-up				
Uncontrolled pick-up		■	■	■
Pick-up 2.00 m		■	■	
Pick-up 2.25 m		□	□	■
Tine rows	Number	5	5	5
Tine spacing	mm	64	64	64
Integrated header plate		■		
Roller pressure pad		□	■	■
Rigid pick-up wheels		■	■	■
Swinging pick-up wheels		□	□	□
Table/rotor				
Without table with conveyor rotor		■	■	
Without table – 2-star conveyor rotor		□	□	
XtraCut – 13 knives with 2-star conveyor rotor			□	
XtraCut – 17 knives with 2-star conveyor rotor with group shift (8-9-17)			□	■
XtraCut – 25 knives with Profi rotor with group shift (12-13-25)				□
Potential cutting length	mm		90 / 70	70 / 45
Fixed bale channel		■		
Hydroflex control bale channel			■	■

FENDT FIXED CHAMBER ROUND BALERS

Equipment variants and technical details.



		1125 F	2125 F	2125 F Profi
Tying				
Varionet net tie		□	■	■
Variotwin twine tie		□	□	□
Net tie/yardage	m	2.000 / 3.000	2.000 / 3.000	2.000 / 3.000
Easy Load System ELS			■	■
Additional net roll holder			□	□
Additional twine box		□	□	□
Bale ejector		□	□	□
Controls				
BalerControl E		■	■	
E-Link			□	■
Chassis				
Trailer axle		■	■	■
Hydraulic brake assembly			□	□
Compressed air brake assembly			□	□
Permitted top speed undamped	km/h	25	25	25
Permitted top speed damped	km/h	40	40	40
Tyres				
15/55 R17		□	□	□
19/45 R17		□	□	□
500/45 R22,5			□	□
500/50 R22,5			□	□
500/60 R22,5			□	□
500/55 R20			□	□